


Hydro

High Pressure Water Blaster



Industrial Park of Shisto | Square 7 | 3rd Street | 18863, Perama | Piraeus - Greece
T: +30 210 43.24.200-1 | F: +30 210 43.29.786
e-mail: sales@zisimopoulos.gr | www.zisimopoulos-sa.gr |  A. Zisimopoulos S.A

Hydro

Hydro 500 is a professional high pressure water blaster, designed and manufactured for use under the toughest conditions. Stainless steel frame with stainless steel cover. Easy to handle, with 4 rubber solid wheels, Hydro 500 is suitable for any cleaning and de-rusting task. Equipped with Nickel plated head pump, for maximum wear and tear resistance.

Features

- Triplex plunger pump, with nickel plated head
- Electric Motor 18.5kW (25HP), S1 duty, class F
- Waterless protection switch
- Adjustable pressure valve
- Auto stop function
- DOL starter with delay timers
- Thermo-protection valve
- Pressure gauge
- Water inlet filter
- Water inlet quick coupling
- Quick screw outlet coupling

Optional Accessories

- Extension high pressure hose 10, 20mtr
- Turbonozzle pack
- Sandblasting pack
- Pipe cleaning hose with micronozzle
- Extension cable 50mtr

Standard Equipment

- 10mtr high pressure hose
- 10mtr waterproof cable
- Spray gun, single lance with quick release nozzle coupling
- High pressure nozzle

Accessories



Extension Cable With Waterproof Connectors




High Pressure Hose



Sandblasting Kit 500 Bar



Turbonozzle



Wall & Surface cleaner

Technical Info



HYDRO		500	350	280	210	150
Voltage/Frequency	V/Hz	3*400/50 Hz 3*440/60 Hz	3*400/50 Hz 3*440/60 Hz	3*400/50 Hz 3*440/60 Hz	3*400/50 Hz 3*440/60 Hz	1*230/50 Hz 1*230/60 Hz
Pressure (max)	bar	500	350	280	210	150
Water Flow (max)	lpm	18	18	15	15	10.5
Motor Power Rating	kW/HP	18.5/25	11/15	7.5/10	5.5/7.5	3/4
Water Inlet Temp. (max)	°C	60	60	60	60	60
Dimensions (W*L*H)	mm	680*900*710	580*750*580	580*750*580	460*650*500	490*670*900
Weight	kg	150	95	83	65	42